

IBF-Graphix

POSFAST

PRODUCT FEATURES

▶ **DIGITAL UV POSITIVE PLATE**

**LONG RUN LENGTH
UP TO 150.000**

ULTRA FAST EXPOSURE

**EXCELLENT DOT RETENTIONS
FOR THE ENTIRE RUN**

**HIGH RESISTANCE
TO ABRASION , SCRATCHING
AND FINGERPRINTS**

**FAST ROLL UP LEADING
TO PAPER AND
INK SAVINGS**

LOW WATER CONSUPTION

POSITIVE UV PLATE FOR CTP DEVICES

IBF TECHNOLOGY

www.ibf.com.br




THE PLATE SPECIALIST

SPECIFICATIONS**► DIGITAL UV POSITIVE PLATE**

Plate type	Positive - working UV plate for CTP devices
Coating	Blue
Image color (exposed)	Blue
Coating	Blue
Spectral sensitivity	360-400 nm
Gauge	0,15mm , 0,20 mm, 0,30 mm, 0,40mm
Lighting conditions	Yellow safe light
Substrate	Electrochemically grained and anodized
Energy	35 - 45 mJ/cm ²
Resolution	1% to 99% at 250 LPI
Operational conditions	40% to 60% RH ; 19°C to 24°C (66°F to 75°F)
Storage conditions	30% to 70% RH ; 15°C to 30°C (59°F to 86°F)
Run length*	Up to 150.000 impressions <small>*Depending on press condition</small>
Processor	Standard positive plate processor

Auxiliary Products

Developer	IBF PD2
Gum	Eco Finisher (SKU 069291) 1 Liter
Baking Solution	IBF SH (SKU 052588) 1Liter
Plate Cleaner	Eco Cleaner (SKU 068425) 1 Liter
Storage Gum	IBF 14 Bè Gum (SKU 002832) 1Liter

www.ibf.com.br**THE PLATE SPECIALIST**

IBF - INDÚSTRIA BRASILEIRA DE FILMES
Rua Lauro Müller, 116 - 10º andar - Botafogo
Rio de Janeiro - RJ - Brazi
CEP:22290-906I
Tel.: +55 21 2103-1000
e-mail: marketing@ibf.com.br